





Head Type / Platform Type	Flush Head / Knurled Platform
Material	Stainless Steel
Finish	Plain



H = Head Diameter
L = Body Length

*Dimensions in millimeters

Part Number	Thread Size		H max.		Hole Size (+0.08)		Sheet Thickness min.		Dist. C/L hole to edge min.		Hole in mating part max.		Tightening Torque(Nm) rec.	
TGFKSP-020***	M2		3.35		1.96		1.0		4.8		2.6		0.20	
TGFKSP-025***	M2.5		4.05		2.47		1.0		5.3		3.1		0.41	
TGFKSP-030***	M3		4.70		2.97		1.0		5.5		3.6		0.84	
TGFKSP-035***	M3.5		5.30		3.48		1.0		6.4		4.1		1.02	
TGFKSP-040***	M4		6.00		3.96		1.0		7.0		4.6		1.92	
TGFKSP-050***	M5		6.70		4.98		1.0		7.0		5.6		3.84	
TGFKSP-060***	M6		8.20		5.97		1.5		8.0		6.6		8.02	
TGFKSP-080***	M8		9.90		7.97		2.0		9.5		8.6		13.50	
Thread Size	Available Lengths(L)													
M2	6	8	10	12	14	15	16	18	20					
M2.5	6	8	10	12	14	15	16	18	20					
M3	6	8	10	12	14	15	16	18	20	25	30			
M3.5	6	8	10	12	14	15	16	18	20	25	30			
M4	6	8	10	12	14	15	16	18	20	25	30			
M5	6	8	10	12	14	15	16	18	20	25	30	40		
M6		8	10	12	14	15	16	18	20	25	30	40	50	60
M8				12	14	15	16	18	20	25	30	40	50	60